

MILWAUKEE TOOL

Milwaukee Electric Tool Corporation BROOKFIELD, WI 53005

Tel: +1 (262) 781-3600 • Fax: +1 (262) 790-6333

Milwaukee Asia Office 29/F, Tower 2, Kowloon Commerce Centre,

51 Kwai Cheong Road, Kwai Chung, Hong Kong Tel: +852-2492-2181 • Fax: +852-2490-4778

Distributed by:

All data incl. service and warranty conditions as well as product range are subject to change without notice Pictures not binding. No liability for printing errors or mistakes. © 2021 Milwaukee Electric Tool Corporation All trademarks are owned by Techtronic Cordless GP unless otherwise stated.

www.milwaukeetool.asia



M18 FUEL **DRIVEN TO OUTPERFORM.**





REDLINK PLUS™ INTELLIGENCE

REDLITHIUM™-ION BATTERY PACK

M18 FSAGV M18 FUEL

100MM / 125MM CORDED BRAKING VARIABLE SPEED POWER **GRINDERS**

GENERATES

INCREASED RAPIDSTOP BRAKE



DRIVEN TO OUTPERFORM.

M18 FUEL is engineered for the most demanding tradesmen in the world. Delivering unrivaled performance in a compact structure, all M18 FUEL products feature three MILWAUKEE exclusive innovations - the POWERSTATE Brushless Motor, REDLITHIUM-ION Battery Pack and REDLINK PLUS Intelligence Hardware and Software - that deliver unmatched power, run-time and durability.

M18 FUEL

most common accessories in the

market



M18 FUEL 100MM / 125MM VARIABLE SPEED BRAKING GRINDERS

GENERATES CORDED POWER



■ POWERSTATE **Brushless Motor** spins at 8,500 RPM, providing power of comparable corded tools

INCREASED CONTROL



- Variable speed control for applications that require lower RPM grinding
- 3500 -8500 RPM
- 5 Speed Settings

RAPIDSTOP BRAKE



- Stops all accessories in under 2 seconds
- Kickback brake protects against bind up situations and reduces risk of kickback



MODELS



M18 FSAGV100XB

VARIABLE SPEED ANGLE GRINDER SLIDE SWITCH



M18 FSAGV125XB

M18 FUEL 125MM BRAKING VARIABLE SPEED ANGLE GRINDER SLIDE SWITCH



M18 FSAGV100XPDB M18 FUEL 100MM BRAKING

VARIABLE SPEED ANGLE GRINDER PADDLE SWITCH

M18 FSAGV125XPDB M18 FUEL 125MM BRAKING VARIABLE SPEED ANGLE

GRINDER PADDLE SWITCH

SPECIFICATIONS

DESCRIPTION	SPECIFICATIONS		DESCRIPTION	SPECIFICATIONS	
	M18 FSAGV100XB M18 FSAGV100XPDB	M18 FSAGV125XB M18 FSAGV125XPDB		M18 FSAGV100XB M18 FSAGV100XPDB	M18 FSAGV125XB M18 FSAGV125XPDI
RPM	3,500 - 8,500		Speed Settings	5	
Grinding Disc Diameter	100 mm	125 mm	Tool-free Guard Change	Yes	
Spindle Thread	M10	M14	Overload Protection	Yes	
Grinding Disc Hole Diameter	16 mm	22.2 mm	Weight (w/M18 B5)	2.6 kg	2.7 kg