

MILWAUKEE TOOL

Milwaukee Electric Tool Corporation BROOKFIELD, WI 53005 USA

Tel: +1 (262) 781-3600 • Fax: +1 (262) 790-6333

Milwaukee Asia Office 29/F, Tower 2, Kowloon Commerce Centre, 51 Kwai Cheong Road, Kwai Chung, Hong Kong

Tel: +852-2492-2181 • Fax: +852-2490-4778

Distributed by:

21/9/2021

All data incl. service and warranty conditions as well as product range are subject to change without notice. Pictures not binding. No liability for printing errors or mistakes. © 2020 Milwaukee Electric Tool Corporation.

All trademarks are owned by Techtronic Cordless GP unless otherwise stated.

www.milwaukeetool.asia



PRIVEN TO OUTPERFORM.





REDLINK PLUS™
INTELLIGENCE

REDLITHIUMTM-ION BATTERY PACK

M18 FH / M18 FHX
M18 FUEL
26MM
CONTROL

CONTROL

M18 FH / M18 FHX

FASTER DRILLING

AUTOSTOP
CONTROL
ENHANCED
SAFETY

104 14MM x 50MM
HOLES
PER CHARGE



DRIVEN TO OUTPERFORM.

M18 FUEL is engineered for the most demanding tradesmen in the world. Delivering unrivaled performance in a compact structure, all M18 FUEL products feature three MILWAUKEE exclusive innovations - the POWERSTATE Brushless Motor, REDLITHIUM-ION Battery Pack and REDLINK PLUS Intelligence Hardware and Software - that deliver unmatched power, run-time and durability.



FILTER

HEPA Filter



26MM SDS PLUS ROTARY HAMMER

FASTER DRILLING



- POWERSTATE **Brushless Motor** delivers 2.7J impact energy for faster drilling speeds
- Less time spent drilling to stay productive

AUTOSTOP CONTROL ENHANCED SAFETY



■ AUTOSTOP Kickback Control Shuts the tool off in a bind up situation, preventing over rotation

UP TO 104 14MM X 50MM HOLES PER CHARGE



Delivers a full day of run-time for most users with the M18 REDLITHIUM-ION HIGH OUTPUT 8.0Ah Batter Pack



SPECIFICATIONS

an on-tool extractor

DESCRIPTION	SPECIFICATIONS	DESCRIPTION	SPECIFICATIONS
Max Capacity	26 mm	Kickback Prevention	Yes
Impact Energy	2.7 J	Anti-Vibration	Yes
RPM	1,330	Dedicated Dust Management	Yes
BPM	4,800	Weight	3.4 kg (FIXTEC: 3.6 kg)